


EDLA BenQ Board

ESSENTIAL series | RE04N

- 
Quad-core SoC
 Excellent performance
- 
Android 13
 The latest & most secure update
- 
40W Built-in Speaker
 20W x 2 speakers
- 
40 Touch Points
 Unleash your creativity
- 
5-in-1 Type-C 65W PD
 Display, audio, touch, data, and 65W power charging







SIAA Certified for Touchscreen
 Antimicrobial property, safety, and appropriate



Germ-Resistant, Eyecare
 Safe-to-Touch for touchscreen, buttons, touch pen, remote control
 Eyecare for Low Blue Light, Flicker Free



IP5X Dust Proof
 To ensure consistent operation
 IEC standard 60529

DISPLAY

Diagonal Size	65", 75", 86"
Display Technology	Zero Bonding
Backlight	DLED
Aspect Ratio	16:9
Resolution	3840 x 2160 (4K)
Brightness (typical)	400 cd/m2
Contrast Ratio	65": 5000:1, 75": 5500:1, 86":4000:1
Dynamic Contrast Ratio	30000:1
LCD Viewing Angle	178°

Color Gamut	72% NTSC
Panel Refresh Rate	60 Hz
Response Time	8 ms
Panel Bit	10-bit
Panel Lifespan	50,000 hours
Operating Hour	18/7
Glass Hardness	9H, Heat-tempered 3.2 mm
Germ-Resistant Technology	Nano-ionic silver
Panel Surface	Anti-Glare, Haze 25%
Display Orientation	Landscape

TOUCH

Touch Technology	Precision IR
Accuracy	±1.0 mm (middle 90% touch area)
Max Touch Points	Up to 40
Touch Resolution	32767 x 32767 px
Object Recognition Range	≥ 3 mm
Touch Response Time	< 10 ms
Touch Interface	USB-B 2.0 x 2
Compatibility	Windows 7/8/10/11/XP macOS/Linux/Android/Chrome OS

COMPUTING

Operating System	Android 13 (Tiramisu)
CPU	Quad-Core (A55 x 4)
GPU	Mali™-G52 MP2
Memory	8GB
Storage	64GB

AUDIOVISUAL

Built-in Speaker	40 Watts (20 W x 2)
Array Microphone	NA
Camera	Optional

CONNECTIVITY

	Front	Rear	Bottom
HDMI In 2.0	x 1	x 2	
HDMI Out 2.0		x 1	
Display port 1.2a		NA	
VGA In			x 1
PC Audio In			x 1
USB-A 3.0 (High speed data transfer & power supply)	x 2	x 2	
USB-A 2.0		x 1	
USB-B 2.0 (Touch)	x 1	x 1	
USB Type-C 3.1 (5-in-1, 65W PD)	x 1		
RS232		x 1	
Earphone (3.5 mm)			x 1
SPDIF out (optical)			x 1
Power (AC) Inlet			x 1
OPS Slot		x 1	
Wake-on-LAN/HDMI/VGA		Yes	
LAN In/Out (RJ45)		x 2	
		OPS: 10/100/1000 Mbps	
		Android: 10/100/1000 Mbps	
Wi-Fi 6.0 (*with protecting cover)		Optional	
Bluetooth 5.2		Optional	

SENSORS

NFC Sensor	NA
Motion Sensor	NA
Air Ionizer	NA
Indoor Air Quality Sensor	NA
Light Sensor	x 1
IR receiver	x 1

POWER

Power Supply	AC 100 to 240V, 50 to 60 Hz
Power consumption (typical)	TBD

DISPLAY LANGUAGES

English/French/German/Dutch/Polish/Russian/Czech/Danish/Swedish/Italian/Romanian/Finnish/Norwegian/Greek/Hungarian/Spanish/Portuguese/Turkish/Traditional Chinese/Simplified Chinese/Arabic/Japanese/Thai/Persian/Korean/Vietnamese/ Indonesian/Hebrew (28L)

SOFTWARE/SOLUTIONS

Device Management Solution	DMS 3.0
Account Management Solution	AMS
Broadcasting Solution	X-Sign Broadcast
Wireless Casting Solution	InstaShare 2
Whiteboarding Solution	EZWrite 6
Floating Tool	Yes
Class Recording	Yes
Scalable canvas	Yes
Handwriting recognition	49 Languages
Co-annotation via intranet	Cloud Whiteboard
Co-annotation via internet (Web browser)	EZWrite 6 Web

ACCESSORIES

Remote Control, Power Code (By Region), Stylus x 2, Quick Start Guide, Regulation Sheet, Touch USB Cable, HDMI Cable, Wi-Fi Dongle Cover


Model	RE6504N	RE7504N	RE8604N
Dimension (WxHxD)	1488.4 × 896.6 × 87.5 mm/	1709.4 × 1020.2 × 87.7 mm/	1957 × 1159.9 × 99.7 mm/
(Without Packing/With Packing)	1628 × 1005 × 208 mm	1863 × 1140 × 225 mm	2110 × 1283 × 225 mm
Net Weight/Gross Weight	34.95 kg/44.70 kg	47.30 kg/60.55 kg	58.55 kg/75.90 kg
VESA Mount/Screws	600 x 400 mm/4 - M8 x 25mm	800 x 400 mm/4 - M8 x 25mm	800 x 600 mm/4 - M8 x 25mm

FRONT BUTTON & I/O



REAR I/O



BOTTOM I/O




Wi-Fi PORT
*with dongle cover

DIMENSION & WALLMOUNT

RE6504N



RE7504N



RE8604N

