

HTI-AP100

Digital Audio Processor

hitrolink

Hitrolink digital audio processor, center brain for ceiling microphone system, it provide strong AI audio processor algorithm and power supply for ACM200 ceiling microphone and speaker. And it support various interface and standard protocol to connect third party devices.

FEATURES SPOTLIGHT

- 3A audio algorithm supported
- AI processor to build balance audio conference environment
- 10*audio line in/out for extra speaker system demand
- Support 8 cascaded microphone power supply
- Small size for flexible installation



SPECIFICATION**Connectivity**

Speaker Interface	Phoenix*8
Line In	3.5mm analog in
Line Out	3.5mm analog out
TRS	6.35mm analog in
Controller	RJ45 connect to HTI-ACT100
Array Mic	RJ45 connect to Hitrolink ceiling microphone
USB-B	TypeB 2.0
USB-A	TypeA 2.0
Reset	Reset button

Power

Input	AC 100-240V, 50/60Hz
Output	DC 48V/5A

General

Product Dimensions	255.4*163.8*45.8mm(10.05*6.45*1.8inches)
Package Dimensions	325*200*117 mm(12.80*7.87*4.61inches)
Gross Weight	2.15kg

Certification

Certification	CE/FCC
---------------	--------

DIMENSIONS (mm[inch])